THERMAL PRINTER CT-S4500

Compatible with large paper sizes, up to 4 inches wide
Allows instant printing of logos and advertisements, or of content containing large volumes of information
Can be used not just for receipts, but for labels as well
The first 4-inch width POS printer from Citizen to output paper from the front
Fastest printing speed in the industry for a 4-inch POS printer, achieving up to 200 mm/second
Flat-topped design allows items to be placed on top of the printer while the printer is in use
Stylish design matches tablet terminals
Will not detract from the atmosphere of stores
New Bluetooth® and wired LAN models available as optional interfaces
Power can be supplied from the printer USB port to customer displays, etc.
A4-sized items can be compressed and printed in designated receipt sizes
ESC/POS emulation allows printing on 4-inch wide paper

Print Width (maximum): 104 mm
Paper Width: 79.5 to 111.5 mm

THERMAL PRINTER CT-S751

All operations such as paper replacement and power ON/OFF can be performed from the front panel
Perfect for placement under shelving
The fastest printer available with front panel operations, achieving printing speeds of up to 350 mm/second
Easy-to-see icon lamps provide at-a-glance understanding of printer status
Smallest height/width in the industry
Can be installed even in the limited space around cash registers or in narrow spaces under shelves
Flat-topped design allows items to be placed on top of the printer while the printer is in use
Design matches tablet terminals
Cash drawers matching the height of the printer are also available
Power can be supplied from the printer USB port to customer displays, etc.

Print Width (maximum): 72 mm
Paper Width: 59 to 80 mm

THERMAL PRINTER CL-E321/CL-E331

Paper width: Variable paper width - 1 inch (25.4 mm) – 4.6 inches (118.1 mm)
Paper load: Hi-Lift™ mechanism and ClickClose™ closure
Printing Speed: Ultra fast print out - up to 200mm per second (8 inches per second)
Paper thickness: Paper thickness up to 0.150mm
Case color: Available in black or white
Media sensor: Black mark sensor, Label gap sensor
**Tear bar:** Upper and lower tear bar

Print Width (maximum): 104 mm
Paper Width: 25.4 to 118.1 mm

THERMAL PRINTER
CL-E300/CL-E303

Paper exit: Front exit, top loading
Paper load: Quick and easy media changing-drop-in paper loading
Printing Speed: Ultra fast print out of receipts-up to 300mm per seconds
Paper thickness: Paper thickness up to 0.150mm
Low space requirement integrated power
supply enables clean work station
Same height as cash drawers
Cash drawer connection
Case color: Available in black or white

Print Width: 58/80 mm
Paper Width: 59 to 80 mm (+/- 0,5 mm)

THERMAL PRINTER
CT-E651

Paper exit: Front exit, top loading
Paper load: Quick and easy media changing - drop-in paper loading
Printing Speed: Ultra fast print out of receipts - up to 300mm per seconds
Paper thickness: Paper thickness up to 0.150mm
Low space requirement - integrated power supply enables clean work station
Same height as cash drawers
Cash drawer connection
Case color: Available in black or white

Print Width (maximum): 72 mm
Paper Width: 59 to 80 mm (+/- 0.5 mm)

THERMAL PRINTER
CT-E351

Paper exit: Front exit, top loading
Paper width: Variable paper width – 58 and 80 mm
Paper load: Quick and easy media changing - drop-in paper loading
Printing Speed: Fast print out of receipts - up to 250mm per seconds
Mobile-POS ready
Same height as cash drawers
Cash drawer connection
Case color: Available in black or white

Print Width (maximum): 72 mm
Paper Width (min to max): 59 to 80 mm (+/- 0,5 mm)

THERMAL PRINTER
CT-S251

Paper exit: Front exit, top loading
Paper width: Paper width 58 mm
Paper load: Quick and easy media changing - drop-in paper loading
Printing Speed: Ultra fast print out of receipts - up to 300mm per seconds
Low space requirement - integrated power supply enables clean work station
Mobile-POS ready
Easy notification - built-in buzzer
Same height as cash drawers
Cash drawer connection
Case color: Available in black or white

Print Width (maximum): 54 mm
Paper Width (min to max): 57.5 mm (+/- 0,5 mm)